

Key Tag

Specifications

Chip	TK28 , TK4100
Operating Frequency	125 kHz (*Option Mifare 13.56MHz)
Material	ABS / PU (ตามรุ่น)
Operating Temperature	-25°C~55°C
Storage temperature	-25°C~50°C



HL-1
Yellow & Blue

วัสดุ: ABS
ขนาด: 43.7*30.5*5.3 mm



HL-3
Yellow & Blue

วัสดุ: ABS
ขนาด: 40.5*32*4.2 mm

HL-2



วัสดุ: ABS
ขนาด: 35.3*28*6.4mm

HL-4



วัสดุ: ABS
ขนาด: 46*28*5mm

HL-5



วัสดุ: ABS
ขนาด: 53*37.5*9.8mm

HL-6



วัสดุ: ABS
ขนาด: 52.5*35.2*9mm

HL-7



วัสดุ: ABS
ขนาด: 55.8*37.3*8.8mm

HL-8



วัสดุ: ABS
ขนาด: 51.4*32.3*5.6mm

HL-9



วัสดุ: ABS
ขนาด: 34.8*23*3.9mm

HL-10



Transparent



วัสดุ: ABS
ขนาด: 55.5*35.5*7mm

HL-11



วัสดุ: ABS
ขนาด: 55*37.5*6.9mm

HL-12



วัสดุ: ABS
ขนาด: 51*40*9mm

HL-13



วัสดุ: ABS
ขนาด: 51*38*8.8mm

HL-14



วัสดุ: ABS
ขนาด: 39*39*5mm

HL-15



วัสดุ: ABS
ขนาด: 53.9*33.8*5mm

HL-16



วัสดุ: ABS
ขนาด: 37.5*31*5.5mm

HL-PU1



วัสดุ: หนัง
ขนาด: 51.2*51.2*6.5mm

HL-PU2



วัสดุ: หนัง
ขนาด: 48*36.2*6.5mm

HL-PU3



วัสดุ: หนัง
ขนาด: 56*36*6.5mm

HL-PU4



วัสดุ: หนัง
ขนาด: 39*39*5.5mm

HL-PU5



วัสดุ: หนัง
ขนาด: 33*48*4.5mm